

PRODUCT SPECIFICATION

產品規格書

產品名稱 Description	產品料號 Part No.	圖號 Drawing No.
DIN41612 IDC Type 2 Rows Female	9001-3632IDCxxA	9001D36003
	9001-3620IDCxxA	9001D36015
	9001-3264IDCxxA	9001D32005

PRODUCT NAME 產品名稱	DOCUMENT No.: 文件編號	Rev. 版本	OUPIIN
DIN41612 IDC Type 2 Rows Female	Q9001-PSS-014	A	歐品電子
	Approved 核准	Checked 審核	Prepared 制作

1. SCOPE 適用範圍

This product specification defines the product performance and the test methods to ascertain the performance of the DIN41612 IDC Type 2 Rows Female Connector, which is designed and manufactured by Oupiin Electronic Co., Ltd. This product specification is applicable but not only for those part numbers which be shown in the cover page.

本產品規格書規定了由歐品電子有限公司設計生產的DIN41612 IDC Type 2 Rows Female型連接器產品的特性及測試方法。本產品規格書適用於但不局限於封面所顯示的產品料號。

2. REFERENCE DOCUMENTS 參考文件

MIL-STD-1344	Test method for electrical connector 電子連接器測試方法
MIL-STD-202	Test method for electrical components 電子零件測試方法
EIA364	Test method for electrical components 電子零件測試方法
JIS C 0051	Test method for electrical components 電子零件測試方法
MIL-G-45204C	Specification for gold plating 鍍金規格
IEC-512-3	IEC standard for current carrying capacity tests IEC電流測試標準
QQ-N-290A	Specification for nickel plating 鍍鎳規格
MIL-P-81728A	Specification for tin/lead plating 鍍錫鉛規格
MIL-T-10727B	Specification for tin plating 鍍錫規格
UL1977	UL standard for safety of attachment plug and receptacle UL安規要求標準
EN/ISO5961	Determination of total lead & cadmium content 總鉛和總鎘含量測定
EN1122	Determination of total lead & cadmium content 總鉛和總鎘含量測定
EN13346	Determination of heavy metals content 重金屬含量測定
EPA3052	Determination of total lead & cadmium content 總鉛和總鎘含量測定

3. FEATURE & DIMENSIONS 特征及尺寸

3.1. PRODUCT DIMENSION 產品尺寸

These connectors shall have the dimensions as shown in drawing.

本產品的相關尺寸參見圖面。

3.2. PCB/PANEL LAYOUT 印刷電路板佈局

The recommended PCB layout is shown in drawing.

本產品適用的 PCB layout 參見圖面。

3.3. BILL OF MATERIAL 材料清單

Harmful material controlling follows the requirements of RoHS. The bill of material is described in drawing.

有害物質控制符合RoHS指令要求。本產品使用的材料參見圖面。

3.4. MECHANICAL & ELECTRICAL CHARACTERISTIC 機械及電氣特性

The connector shall have the mechanical and electrical performance as described in drawing.
本產品的機械及電氣特性參見圖面。

3.5. PACKAGING 包裝

Products shall be packaged according to requirements specified in purchase order for safe delivery, connector container and the packaging method are shown in package specification.
產品可依客戶指定要求包裝，包裝材料與包裝方式參見產品包裝規範。

3.6 RATING CURRENT AND RATING VOLTAGE 額定電流與額定電壓

Rating current is 2.0A, rating voltage is 500V DC/AC RMS.
額定電流 2.0A，額定電壓 500V DC/AC RMS。

3.7 STORAGE AND OPERATING TEMPERATURE 存貯與使用溫度

Temperature range: -55°C~+125°C, including terminal temperature rise for rating current.
溫度範圍：-55°C~+125°C，包含接觸端子的額定電流溫升。

4. PERFORMANCE AND TEST DESCRIPTION 性能及測試**4.1. REQUIREMENT 要求**

Product is designed to meet electrical, mechanical, and environmental performance requirements specified in Table I.
本產品設計符合附表一所列的機械，電氣及環境要求。

4.2. TEST CONDITION 測試條件

Unless otherwise specified, all tests shall be performed at ambient environmental conditions.
除非特別注明，所有測試在室溫條件下完成。

4.3. SAMPLE SELECTION 樣品選擇

Test samples shall be selected at random from current production. No test samples shall be reused. Samples are pre-conditioned with 10cycles of durability. Each group shall be containing 5 test samples at least.
測試樣品從現生產的產品中隨機抽取，所有測試過的樣品不得重複使用。樣品已預先插拔10次，每組測試至少有5個樣品。

4.4. TEST SEQUENCE 測試順序

Product qualification test sequence as shown in Table II.
產品品質測試順序見附表二。

Table I: Test Requirements and Methods

附表一：測試要求與方法

Items 項目	Requirements 要求	Test Methods 測試方法
1. Confirmation of Product 產品確認	Product shall be conforming to the requirements of applicable product drawing. 產品必須符合相關產品圖面的要求。	Visually, dimensions and functionally inspected per applicable product drawing. 依相關產品圖面，檢查產品的外觀、尺寸及功能。
2. Contact Resistance 接觸阻抗	20 mΩ Max. initial. 初始狀態最大 20 mΩ。	Subject mated contacts assembled in housing to closed circuit of 100 mA max. 20 mV max. MIL-STD-202, Method 307. 所述固定在外殼裏的端子連結到一個封閉回路中測試，電流 100 mA max，電壓 20 mV max。適用：MIL-STD-202，方法 307。
3. Insulation Resistance 絕緣阻抗	1000 MΩ Min. 最小 1000 MΩ。	Measure by applying test potential between the adjacent contacts, and between the contacts and ground in the mated connector. MIL-STD-202, Method 302, Condition B (500 V DC±10%). 測試產品相鄰端子間以及端子與接地間的電阻，適用：MIL-STD-202，方法 302，條件 B (500 V DC±10%)。
4. Dielectric Withstanding Voltage 耐電壓	Connector must withstand test potential of 1000 VAC RMS for 1 minute, current leakage must be 0.2mA Max. 產品必須承受測試電壓 1000 VAC RMS，時間 1 分鐘，漏電流不大於 0.3 mA。	Measure by applying test potential between the adjacent contacts, and between the contacts and ground in the mated connector. MIL-STD-202, Method 301. 對產品相鄰端子間以及端子與接地間加載電壓，並測試其漏電流。適用：MIL-STD-202，方法 301。
5. Durability (Repeated Mating/Un-mating) 耐久性	Contact Resistance: 30 mΩ Max. after testing. 測試後接觸阻抗最大 30 mΩ。	Repeat mate and unmated for connector 400 cycles, at a speed of 10 cycles per minute. 重復進行配合產品 400 次插拔，速度每分鐘 10 次。
6. Connector Pin Mating /Un-mating Force 單支端子插入力/拔出	Mating force: 0.9 N/Pin Max. Un-mating force: 0.15 N/Pin Min. 插入力最大 0.9 N/Pin，拔出	At a speed of 25±3 mm/minute, apply axial insert the mating part into fully or pull out from the subject product. 以 25±3 mm/分鐘的速度，軸向完全插入對配插件到被測產品中或從被測產品中拔出。
7. Contact Retention Force 端子保持力	6 N/Pin. Min. 最小 6 N/Pin。	Apply axial pull out force at a speed of 25±3 mm/minute on the contact assembled in the housing.



PRODUCT SPECIFICATION OF Ouplin

		以 25±3mm/分鐘的速度施加軸向拉力從塑膠本體上拔出端子。
8. Vibration Sinusoidal Low Frequency 低頻正弦振動	No electrical discontinuity greater than 1 μs shall occur, Contact Resistance: 30 mΩ Max. 不允許出現超過 1 μs 的瞬間斷開，接觸阻抗最大 30 mΩ。	Subject mated connector to 10-55-10 Hz traversed in 1 minute at 1.5 mm amplitude, 2 hours each of 3 mutually perpendicular planes, 10 mA potential applied. MIL-STD-202, Method 201. 對測試產品，在頻率變化每分鐘從 10-55-10 Hz, 振幅 1.5 mm 條件下，在互相垂直的三個面上，每個面 2 小時下測量，電流 10 mA。適用：MIL-STD-202，方法 201。
9. Thermal Shock 熱衝擊	After testing, no damage, Contact Resistance 30 mΩ Max. Dielectric Strength should be OK, Insulation Resistance should be 1000 MΩ Min. 測試後產品無損壞，接觸阻抗最大 30mΩ；耐電壓測試 OK，絕緣阻抗最小 1000 MΩ	Temperature range from -55°C to +85°C. Start from -55°C, after 30 minutes, change to +85°C; change time is no more than 30 seconds, total 5 cycles. MIL-STD-202, Method 107, condition A.溫度變化範圍：-55°C~+85°C。從 -55°C 開始，30 分鐘後換到+85°C，轉換時間不超過 30 秒，共 5 個循環。適用：MIL-STD-202，方法 107，條件 A。
10. Humidity (Steady State) 恆溫恆濕	After testing, no damage, Contact Resistance 30 mΩ Max. Dielectric Strength should be OK, Insulation Resistance should be 1000 MΩ Min. 測試後產品無損壞，接觸阻抗最大 30mΩ；耐電壓測試 OK，絕緣阻抗最小 1000 MΩ。	Temperature: 40±2°C. Relative Humidity: 90-95%. Duration: 96 Hours. MIL-STD-202, Method 103, condition B. 溫度：40±2°C。相對濕度：90-95%。持續時間：96 小時。適用：MIL-STD-202，方法 103，條件 B。
11. Salt Spray 鹽霧	After testing, no damage, Contact Resistance 30 mΩ Max. Dielectric Strength should be OK; Insulation Resistance should be 1000 MΩ Min. 測試後產品無損壞，接觸阻抗最大 30mΩ；耐電壓測試 OK，絕緣阻抗最小 1000 MΩ。	5±1% salt concentration 48 hours 35±2°C MIL-STD-202, Method 101, condition B. 鹽水濃度 5±1%，時間 48 小時，溫度 35±2°C。適用：MIL-STD-202，方法 101，條件 B。
12. High Temperature Life 高溫老化	After testing, no damage, Contact Resistance 30 mΩ Max. Dielectric Strength should be OK; Insulation Resistance should be 1000 MΩ Min. 測試後產品無損壞，接觸阻抗最大 30mΩ；耐電壓測試 OK，絕緣阻抗最小 1000 MΩ。	Subject product to 125±3°C for 96 hours continuously. MIL-STD-202, Method 108, condition A. 產品置於 125±3°C 連續 96 小時。適用：MIL-STD-202，方法 108，條件 A。

Table II: Product Qualification Test Sequence
附表二：產品測試順序

Test Description 測試描述	Test Group 測試分組							
	A	B	C	D	E	F	G	H
1. Conformation of Product 產品確認	1,7	1,4	1,9	1,9	1,9	1,3	1,9	1,9
2. Contact Resistance 接觸阻抗	2,6		2,6	2,6	2,6		2,6	2,6
3. Insulation Resistance 絕緣阻抗	3		3,7	3,7	3,7		3,7	3,7
4. Dielectric Withstanding Voltage 耐電壓	4		4,8	4,8	4,8		4,8	4,8
5. Durability (Repeated Mating/Un-mating) 耐久性	5							
6. Connector Pin Mating/Un-mating Force 單支端子插入/拔出力						2		
7. Contact Retention Force 端子保持力		3						
8. Vibration Sinusoidal Low Frequency 低頻正弦振動			5					
9. Thermal Shock 熱衝擊				5				
10. Humidity (Steady State) 恆溫恆濕					5			
11. Salt Spray 鹽霧							5	
12. High Temperature Life 高溫老化								5